

Danubio LP



Models: 1515 LP/2015 LP



Models: 1211 LP/1510 LP



Models: 1515 LP/2015 LP

Standard equipment:


- 3.700.0036 Gun M22 - 3/8 (mod 1211 LP/1510 LP).



- 3.700.0030 Gun M22 - 3/8 with rotating coupling (mod. 1515 LP/2015 LP).



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0047 Nozzle type 030 (mod. 1510 LP)
- 3.103.0052 Nozzle type 055 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)



- 4.618.0049 High pressure hose 8 m (mod. 1211 LP/1510 LP).
- 4.618.0143 High pressure hose 10 m (mod. 1515 LP/2015 LP).



- Power cable 5 m

Optional:

- High-pressure hose-reel with 10 m h.p. hose cod. 6.608.0021

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (models 1515/2015).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Suction and delivery S/S valves.
- Low voltage and delayed Total Stop (models 1515/2015).
- Detergent built-in tank for indirect suction.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose-reel (**optional**).
- Accessory holder.
- Power cable holder.
- Ergonomic handle.

VERSION
60 Hz
AVAILABLE
DETAILS PAGE 9

	Danubio 1211 LP	Danubio 1510 LP	Danubio 1515 LP	Danubio 2015 LP
code	8.659.0001	8.659.0009	8.659.0012	8.659.0013
operat. pressure/max	120/150 bar-1740/2175 psi	150/160 bar-2175/2320 psi	150 bar-2175 psi	200 bar-2900 psi
delivery rate	660 l/h-2.91 GPM	540 l/h-2.38 GPM	900 l/h-3.96 GPM	900 l/h-3.96 GPM
abs. power/voltage	3000W - 230V~50Hz 1 ph	3000W - 230V~50Hz 1 ph	5000W - 400V~50Hz 3 ph	7000W - 400V~50Hz 3 ph
motor/pump type/RPM	MP3/1450 RPM	MP3/1450 RPM	MPW3/1450 RPM	MPW3/1450 RPM
max. water inlet temperature	40 °C	40 °C	40 °C	40 °C