

HyperT

GUARANTEED



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Integrated elastic joint, for best pump coupling (three phase models).
- Low voltage and delayed Total Stop.
- Vertical burner with high thermal efficiency steel coil.
- Auxiliary motor for burner air-cooling and two ways fuel pump.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Header tank and antiscaling device.
- Pressure accumulator for hose and gun vibrations prevention (only 2015/2021 models).
- Hose-reel (**optional**).



Only
2021 LP - 2015 LP



Integrated elastic joint, for best pump coupling

Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0050 Nozzle type 045 (mod. 2015 LP)
- 3.103.0055 Nozzle type 070 (mod. 2021 LP)
- 3.103.0049 Nozzle type 040 (mod. 2515 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

Optional:

- Hose-reel with brake (hose not included) cod.6.608.0010
- Antiscaling LC-PRECAL (pcs. 4 x 5 ft.) cod. 3.697.0044

VERSION
60 Hz
AVAILABLE
DETAILS PAGE 33

	HYPER T 2015 LP	HYPER T 2021 LP	HYPER T 2515 LP
code	8.623.0911	8.623.0902	8.623.0928
operat. pressure	200 bar-2900 psi	200 bar-2900 psi	250 bar-3600 psi
delivery rate	900 l/h-3.96 GPM	1260 l/h-5.55 GPM	900 l/h-3.96 GPM
abs. power/voltage	7300W - 230V~50Hz 1ph	9700W - 400V~50Hz 3 ph	8700W - 400V~50Hz 3 ph
motor/pump type/RPM	MPW5/1450 RPM	MPW5/1450 RPM	MPW5/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C