

# HyperL GUARANTEED (single phase)



**Equipped with:**

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Low fuel lamp and cut off.
- Safety valve.
- Detergent built-in tank for indirect suction.
- Glycerine pressure gauge.
- Auxiliary motor for burner air cooling and mechanical two ways fuel pump.
- Hose-reel (optional).



**Standard equipment:**

- 3.700.0036 Gun M22 - 3/8"



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

**Optional:**

- Hose-reel with brake (hose not included)  
cod.6.608.0018



HYPER L 1211 LP	
code	8.621.0921
operat. pressure/max	110/150 bar-1595/2175 psi
delivery rate	660 l/h-2.91 GPM
abs. power/voltage	3000W - 230V~50Hz 1ph
motorpump type/RPM	MP3/1450 RPM
max. temp. inlet/outlet	40/140 °C